

# “ T I T A N I U M D I O X I D E ”

## AIO R2000

### Product Description

**AIO R2000** is a kind of Micronized Rutile Titanium Dioxide which has not any surface treatment. It provides excellent hiding power, good whiteness and dispersion, suitable for the products without high requirements on weather resistance.

### Advantages:

Excellent hiding power | Good whiteness | Cost saving

Typical Properties	Specification	Test Method
TiO <sub>2</sub> Content	≥99.0%	ISO591-1
Volatile matter at 105°C	≤0.5%	ISO787-2
Resistivity of aqueous extract	≥50Ω-M	ISO787-14
Residue on sieve (45μm)	≤0.05%	ISO787-18
PH value	6.5-8.0	ISO787-9
Oil absorption	≤19g/100g	ISO787-5
Specific gravity	4.2g/cm <sup>3</sup>	ISO787-10

### Recommended Applications:

Optimal applications in primer paints, middle layer coating, road-marking paint, interior coating, plastics which has no high requirements on weather resistance.

### Packaging:

In 25 kg multi-ply paper bag or 500kg, 1000kg bulk bag.

### Storage:

The products should not be stored in outside areas and avoiding direct contact with moisture.

### Safety Instructions:

Always wear gloves and protective clothes when handling this products. More information about the product, please see the MSDS or contact us directly.

All information given and recommendations made herein are based upon research and are believed to be accurate. Since the application process and conditions of use of our products are beyond our control, all recommendations and suggestions are made without guarantee.